

VM3 - VIDEO + RS232



The OPTRAL Series VM3 allows the transmission of one standard video signal and one RS232 data channel over multimode optical fibre. One transmitter and one receiver using multimode fibres form the basic system. The Series VM3 includes models to transmit and receive video and data signals over one single fibre.

All the models comply with the requirements according to the Electromagnetic Compatibility and Low Tension Standards (CE Marking).

FEATURES

- Multimode optical fibre
 - Wavelength 850 nm and 1300 nm
 - Modular Units and Rack Cards
 - Configurable for short and long distances
 - Optical connectors: ST ⁽¹⁾
- (1) For other optical connectors, consult us.

POWER/TEMPERATURE/SIZE

- Temperature = 0° ÷ +50°C
- Humidity = 10% ÷ 90%
- 12 Vdc / 400 mA
- Modular Units:
 - Type M = 179 x 127 x 32 mm
- Rack Cards = 1 Slot Rack

VIDEO SIGNAL

- I/O Impedance = 75 Ω
- Bandwidth = 10 MHz
- Differential Gain < 2%
- Differential Phase < 2°
- I/O Video connector = BNC

RS232 DATA

- Data Rate ≤ 57600 bps
- Bit Error Rate ≤ 10⁻⁹
- Operating mode = Asynchronous / Full Duplex
- Without Handshake
- Connector RS232 = SubD-9

ACCESORIES (NOT INCLUDED)

- Modular Units (Power Supplies)
 - Type M = Model PS155
- Rack Cards
 - Card Cage 3U (Rack 19") = PR100

.....

VM3 - VIDEO + RS232

AVAILABLE MODELS

PART NUMBER	DESCRIPTION	FORMAT	NUMBER FIBRES	MAXIMUM ATTENUATION (2)	WAVELENGTH
VM301-TB1	1 Tx Video + Rx RS232 Modular	Type M	2	14 dB	850 nm
VM301-TR1	1 Tx Video + Rx RS232 Rack	Rack			
VM301-RB1	1 Rx Video + Tx RS232 Modular	Type M			
VM301-RR1	1 Rx Video + Tx RS232 Rack	Rack			
VM301-TB2	1 Tx Video + Rx RS232 Modular	Type M	2	14 dB	1300 nm
VM301-TR2	1 Tx Video + Rx RS232 Rack	Rack			
VM301-RB2	1 Rx Video + Tx RS232 Modular	Type M			
VM301-RR2	1 Rx Video + Tx RS232 Rack	Rack			
VM301-TB5	1 Tx Video + Rx RS232 Modular	Type M	1	12 dB	850/1300 nm
VM301-TR5	1 Tx Video + Rx RS232 Rack	Rack			
VM301-RB5	1 Rx Video + Tx RS232 Modular	Type M			
VM301-RR5	1 Rx Video + Tx RS232 Rack	Rack			
VM302-TB1	1 Tx Video + Tx/Rx RS232 Modular	Type M	2	14 dB	850 nm
VM302-TR1	1 Tx Video + Tx/Rx RS232 Rack	Rack			
VM302-RB1	1 Rx Video + Tx/Rx RS232 Modular	Type M			
VM302-RR1	1 Rx Video + Tx/Rx RS232 Rack	Rack			
VM302-TB2	1 Tx Video + Tx/Rx RS232 Modular	Type M	2	14 dB	1300 nm
VM302-TR2	1 Tx Video + Tx/Rx RS232 Rack	Rack			
VM302-RB2	1 Rx Video + Tx/Rx RS232 Modular	Type M			
VM302-RR2	1 Rx Video + Tx/Rx RS232 Rack	Rack			
VM302-TB5	1 Tx Video + Tx/Rx RS232 Modular	Type M	1	12 dB	850/1300 nm
VM302-TR5	1 Tx Video + Tx/Rx RS232 Rack	Rack			
VM302-RB5	1 Rx Video + Tx/Rx RS232 Modular	Type M			
VM302-RR5	1 Rx Video + Tx/Rx RS232 Rack	Rack			

(2) Maximum attenuation at 62.5/125. For 50/125 reduce optical budget by 3dB.
 Type M = 179 x 127 x 32 mm

•••••