

VM5 - VIDEO + TTL



The OPTRAL Series VM5 allows the transmission of one standard video signal and one TTL data channel over multimode optical fibre. One transmitter and one receiver using multimode fibres form the basic system. The Series VM5 includes models to transmit and receive video and data signals over one single fibre.

All the models comply with the requirements according to the Electromagnetic Compatibility and Low Tension Standards (CE Marking).

FEATURES

- Multimode optical fibre
- Wavelength 850 nm and 1300 nm
- Modular Units and Rack Cards
- Configurable for short and long distances
- Optical connectors: ST ⁽¹⁾

(1) For other optical connectors, consult us.

POWER/TEMPERATURE/SIZE

- Temperature = 0° ÷ +50°C
- Humidity = 10% ÷ 90%
- 12 Vdc / 400 mA
- Modular Units:
 - Type M = 179 x 127 x 32 mm
- Rack Cards = 1 Slot Rack

VIDEO SIGNAL

- I/O Impedance = 75 Ω
- Bandwidth = 10 MHz
- Differential Gain < 2%
- Differential Phase < 2°
- I/O Video connector = BNC

TTL DATA

- Data Rate ≤ 57600 bps
- Bit Error Rate ≤ 10⁻⁹
- Operating mode = Asynchronous / Full Duplex
- Up Level > 2.4 V / Low Level < 0.8 V
- TTL connector = Screw Terminal CI (6 pin)

ACCESORIES (NOT INCLUDED)

- Modular Units (Power Supplies)
 - Type M = Model PS155
- Rack Cards
 - Card Cage 3U (Rack 19") = PR100

.....

VM5 - VIDEO + TTL

AVAILABLE MODELS

PART NUMBER	DESCRIPTION	FORMAT	NUMBER FIBRES	MAXIMUM ATTENUATION (2)	WAVELENGTH
VM501-TB1	1 Tx Video + Rx TTL Modular	Type M	2	14 dB	850 nm
VM501-TR1	1 Tx Video + Rx TTL Rack	Rack			
VM501-RB1	1 Rx Video + Tx TTL Modular	Type M			
VM501-RR1	1 Rx Video + Tx TTL Rack	Rack			
VM501-TB2	1 Tx Video + Rx TTL Modular	Type M	2	14 dB	1300 nm
VM501-TR2	1 Tx Video + Rx TTL Rack	Rack			
VM501-RB2	1 Rx Video + Tx TTL Modular	Type M			
VM501-RR2	1 Rx Video + Tx TTL Rack	Rack			
VM501-TB5	1 Tx Video + Rx TTL Modular	Type M	1	12 dB	850/1300 nm
VM501-TR5	1 Tx Video + Rx TTL Rack	Rack			
VM501-RB5	1 Rx Video + Tx TTL Modular	Type M			
VM501-RR5	1 Rx Video + Tx TTL Rack	Rack			
VM502-TB1	1 Tx Video + Tx/Rx TTL Modular	Type M	2	14 dB	850 nm
VM502-TR1	1 Tx Video + Tx/Rx TTL Rack	Rack			
VM502-RB1	1 Rx Video + Tx/Rx TTL Modular	Type M			
VM502-RR1	1 Rx Video + Tx/Rx TTL Rack	Rack			
VM502-TB2	1 Tx Video + Tx/Rx TTL Modular	Type M	2	14 dB	1300 nm
VM502-TR2	1 Tx Video + Tx/Rx TTL Rack	Rack			
VM502-RB2	1 Rx Video + Tx/Rx TTL Modular	Type M			
VM502-RR2	1 Rx Video + Tx/Rx TTL Rack	Rack			
VM502-TB5	1 Tx Video + Tx/Rx TTL Modular	Type M	1	12 dB	850/1300 nm
VM502-TR5	1 Tx Video + Tx/Rx TTL Rack	Rack			
VM502-RB5	1 Rx Video + Tx/Rx TTL Modular	Type M			
VM502-RR5	1 Rx Video + Tx/Rx TTL Rack	Rack			

⁽²⁾ Maximum attenuation at 62.5/125. For 50/125 reduce optical budget by 3dB.
Type M = 179 x 127 x 32 mm

