

DM3 - TTL DATA



The OPTRAL Series DM3 allows the transmission and reception of TTL data signals over multimode optical fibre. Two transceivers and two optical fibres form the basic system. One special model has been designed for transmission and reception over one single fibre.

All the models comply with the requirements according to the Electromagnetic Compatibility and Low Tension Standards (CE Marking).

FEATURES

- Multimode Optical Fibre
 - Wavelength 850 nm and 1300 nm
 - Modular Units and Rack Cards
 - Configurable for short and long distances
 - Optical connectors: ST ⁽¹⁾
- ⁽¹⁾ For other optical connectors consult us.

POWER / TEMPERATURE / SIZE

- Temperature = 0° ÷ +50°C
- Humidity = 10% ÷ 90%
- 12 Vdc / 200 mA
- Modular Units
 - Type S = 105 x 95 x 32 mm
- Rack Cards = 1 Slot Rack

TTL DATA

- Data Rate ≤ 115 Kbs
- Bit Error Rate ≤ 10⁻⁹
- Operating mode = Asynchronous / Full Duplex
- Up Level > 2.4 V / Dow Level < 0.8 V
- TTL connector = Screw Terminal CI (6 pin)

ACCESORIES (NOT INCLUDED)

- Modular Units (Power Supplies)
 - Type S = Model PS150
- Rack Cards
 - Card Cage 3U (Rack 19") = PR100

•••••

POL. IND. MAS ROGER. C/ BENJAMÍN FRANKLIN, S/N. 08397 PINEDA DE MAR (BARCELONA) TEL. +34-902 40 12 13 FAX +34-937 62 58 31
<http://www.optral.com> E-Mail: optral@optral.com

DM3 - TTL DATA

AVAILABLE MODELS

PART NUMBER	DESCRIPTION	FORMAT	NUMBER FIBRES	MAXIMUM ATTENUATION ⁽²⁾	WAVELENGTH
DM301-XB1	Transceiver TTL Modular	Type S	2	16 dB	850 nm
DM301-XR1	Transceiver TTL Rack	Rack			
DM301-XB2	Transceiver TTL Modular	Type S	2	16 dB	1300 nm
DM301-XR2	Transceiver TTL Rack	Rack			

⁽²⁾ Maximum attenuation at 62.5/125. For 50/125 reduce optical budget by 3dB.
 Type S = 105 x 95 x 32 mm

•••••