


.....

OPTRAL

CDI-M



Military Distribution Cable (Up to 12 FO)



Cable Description

- 01. Tight Buffer Fibre (0.9 mm)
- 02. Aramid
- 03. Outer Jacket

Norms / Approvals

Based on military norm MIL-C-85045

Options

- Easy-Strip Buffer
- PU-LSZH Jacket



Advantages

Compact / Lightweight / Flexible / Easy to strip (gel free) / Totally dielectric / Reduced diameter / Direct connectorization / Based on military norm.



All technical specifications are subject to change without prior notice. Consult OPTRAL for the latest edition.

SPECIFICATIONS

	2	4	6	8	10	12
Fibres	2	4	6	8	10	12
Strength Members	Aramid Yarns					
Outer jacket	Polyurethane					
Colour	Black					
Weight (Kg/Km)	21	24	29	36	45	49
Outer Ø (mm)	5.1 ± 0.3	5.5 ± 0.3	5.6 ± 0.3	6.2 ± 0.3	6.4 ± 0.3	6.7 ± 0.3
Tensile Load Perm / Inst (N)	600 / 1100				700 / 1250	
Crush (N)	2000					
Temperature Range	-40°C to +70°C					
Min. Bending Radius	20 x Outer Ø					
Maximum Length	4200 m					

Colour Fibres : Blue – Orange – Green – Brown – Grey – White – Red – Black – Yellow – Violet – Pink – Turquoise

.....