


.....

OPTRAL



Mini CDIR-M

Militar Breakout Cable (Up to 12 FO)



Descripción cable

- 01. Tight Buffer Fibre (0.9 mm)
- 02. Aramid
- 03. Individual Jacket (Ø 2.0 mm)
- 04. Aramid
- 05. Ripcord
- 06. Outer Jacket

Norms / Approvals

Based on military norm MIL-C-85045

Options

- Easy-Strip Buffer
- PU-LSZH Jacket



All technical specifications are subject to change without prior notice. Consult OPTRAL for the latest edition.

Advantages

Compact / Resilient / Tough / Excellent mechanical resistance / Easy to strip (gel free) / Totally dielectric / Direct connectorization / Based on military norm



TOTALLY DIELECTRIC



MOISTURE PROTECTED



HIGH FLEXIBILITY



ULTRAVIOLET RESISTANCE

SPECIFICATIONS

	2	4	6	8	12
Fibres	2	4	6	8	12
Subcables strength members	Aramid Yarns				
Subcables Ø (mm)	2.0				
Subcables jacket	Thermoplastic LSZH ¹				
Identification	Colours ²				
Outer jacket	Polyurethane				
Colour	Black				
Weight (Kg/Km)	50	50	67	93	98
Outer Ø (mm)	7.8 ± 0.3	7.8 ± 0.3	9.0 ± 0.3	10.4 ± 0.5	11.0 ± 0.5
Tensile Load Perm / Inst (N)	800 / 1450	1000 / 1800	1200 / 2150	1400 / 2500	1800 / 3250
Crush (N)	2000				
Temperature Range	-40 °C to +70 °C				
Min. Bending Radius	20 x Outer Ø				
Max. Length	4200 m				

¹ LSZH – Halogen free, low smoke and flame retardant thermoplastic compound.

² Colour Fibres = Blue, orange, green, brown, grey, white, red, black, yellow, violet, pink, turquoise.

.....